



ErgoDeck with Integrated No-Slip Cleats - Open

Group 553

A high traction, non-slip flooring engineered to outperform and outlast traditional gritted products. ErgoDeck with Integrated No-Slip Cleats [552,553] delivers a sure-footed work surface for maximum productivity, performance, and safety...in even the most demanding workplace conditions! The exclusive "cleated design"—modeled after the cleats that professional athletes wear for traction—overcomes harsh and slick workplace conditions and provides a sure-footed, remarkably resilient standing surface. Slips, trips, and falls is the 3rd leading cause of missed workdays and the 4th leading cause of work-related death, averaging over \$41,000 per claim. No-Slip Cleats addresses these issues directly, providing a common-sense alternative to hard and slick concrete. With the use of ErgoDeck No-Slip Cleats, companies can eliminate messy gritted products once and for all. Gritted mats give some temporary traction but wear with use and become slippery with saturation. Unlike gritted mats—which cannot be maintained and cleaned—ErgoDeck with No-Slip Cleats can withstand power washing, scrubbing, and aggressive cleaning. When the problem is slick, dangerous, and unforgiving floors, ErgoDeck with No-Slip Cleats is the definitive solution

Costs 28% less than gritted products

Eliminate the high cost of slips, trips, and falls

The average cost of a slip, trip, and fall claim is **\$41K** and at **\$85K**, resulting head injuries are the highest claim. (NSC)

Trip and fall incidents are also responsible for the highest fatality rate costing **\$1.4M** (NSC)

- U.S. PATENT NO. D704,961; D502,557; D520,650
- Unmatched slip prevention
- Customize in 3 inch increments to fit any area or configuration
- Can withstand powerwashing and aggressive maintenance
- Outperforms and outlasts grit
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Type	Non-slip Safety Flooring
Suitable Environment	Wet, Oily, Slippery
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Drainage
Compound	PVC
Recycled	>80%

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / less than 1% loss
Temperature Range	10 to 110 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.10 / Wet: COF = 1.10
Compression Deflection	ASTM D575-91 / 10%

Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
553.78x18x18BK-CS10	715411681181	Black	0.875	18" x 18"	Y	CS-10
553.78x18x18CH-CS10	715411681181	Black	0.875	18" x 18"	Y	CS-10